

4500 liter tank i Rostfritt 304



118 000 SEK /st exkl moms

Additional information: Milk; Double jacket with trickle ring - suitable for unpressurized temperature control; a rectangular plate was cut out of the double jacket (this plate is inside the tank; see photos); former connections partially cut off or welded shut

Volumetric volume (L): 4.500 L

Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)
Model: vertical

Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no
Total discharge: yes

Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no
Registration plate on the tank: no

Flange for agitator: no
Position of manway: headside
Outlet of tank: DN100 DIN 11851
Agitator: yes
Number of revolutions: 24 / 49

Power: 1.2 / 2.2
Internal diameter tank: 1.990 mm
Outer diameter tank: 2.100 mm
Cylinder height: 1.220 mm
Total height of tank: 2.850 mm

SKU: 308983

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: single jacketed with heat-exchanger

Mobil tank: Nej

Övrig information: Milk; Double jacket with trickle ring – only suitable for pressureless cooling; a rectangular sheet was cut out of the double jacket (this sheet is located inside the tank; see photos); former

Övrig information2: connections partially cut off or welded shut; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 4500

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 1.220 mm

Invändig diameter: 1.990 mm

Total höjd: 2.850 mm

Ytterdiameter: 2.100 mm

Omrörare

Kraft (kW): 1.2 / 2.2

Varvtal: 24 / 49

Mer

Isolerad: Nej