

4500 liter tank i Syrafast 316



88 000 SEK /st exkl moms

Additional information: Dairy; Smaller dents in the inner cylinder; Manhole cover screw connections incomplete; Tank 1 (F9): outlet DN 65 DIN 11851 with butterfly valve; 1 smaller dent in the insulation jacket; Tank 2 (F7): outlet end (diameter 65 mm) cut off (see photos)

Volumetric volume (L): 4.500 L

Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 316 (V4A)
Model: vertical

Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no
Total discharge: yes

Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no
Position of manway: in the bottom

Outlet of tank: available
Agitator: yes
Number of revolutions: 17
Power: 1,10
Internal diameter tank: 1.940 mm

Outer diameter tank: 2.060 mm
Cylinder height: 1.400 mm
Total height of tank: 3.200 mm
Empty weight tank: 950

SKU: 281728

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated

Mobil tank: Nej

Övrig information: Dairy; Smaller dents in the inner cylinder; Manhole cover screw connections incomplete; Tank 1 (F9): outlet DN 65 DIN 11851 with butterfly valve; 1 smaller dent in the insulation jacket; Tank 2

Övrig information2: (F7): outlet end (diameter 65 mm) cut off (see photos); we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 4500

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.400 mm

Invändig diameter: 1.940 mm

Total höjd: 3.200 mm

Ytterdiameter: 2.060 mm

Omrörare

Kraft (kW): 1,10

Varvtal: 17

Mer

Isolerad: Ja

Vikt: 950