

4500 liter tank i Syrafast 316



102,000,00 kr /st exkl moms

Additional information: Chemistry; Half-coils cylinder only in the lower cylinder area; some residues of previous content

Volumetric volume (L): 4.500 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Max Overpressure: 6 Bar

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: cylinder

Outlet of tank: 55

Agitator: yes

Number of revolutions: 1.445

Power: 5,50

Internal diameter tank: 1.500 mm

Cylinder height: 2.390 mm

Total height of tank: 4.550 mm

SKU: 273121

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: single jacketed with heat-exchanger

Mobil tank: Nej

Övrig information: Chemistry; Half-coils cylinder only in the lower cylinder area; some residues of previous content; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 4500

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 2.390 mm

Invändig diameter: 1.500 mm

Total höjd: 4.550 mm

Omrörare

Kraft (kW): 5,50

Varvtal: 1.445

Mer

Isolerad: Nej
