458 liter tank i Syrafast 316



100 000 SEK /st exkl moms

Additional information: pharmacy; Filling pipe inside the tank (see pictures)
Volumetric volume (L): 458 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 42 L
Max Overpressure: 6 Bar

Max onderdruk: 1 Bar
Max. working temperature: 150 °C
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Heat exchanger: RVS 304

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: clamp

Agitator: yes
Number of revolutions: 700
Power: 0,44
Internal diameter tank: 780 mm
Cylinder height: 750 mm

Total height of tank: 2.000 mm

SKU: 481855

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 150 °C
Mobil tank: Nej
Övrig information: pharmacy; Filling pipe inside the tank (see pictures); we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator
Omrörare: Ja
Övertryck: 3 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 458

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank
Cylinderhöjd: 750 mm
Invändig diameter: 780 mm
Total höjd: 2.000 mm

Omrörare
Kraft (kW): 0,44
Varvtal: 700

Mer
Värmeväxlare: RVS 304
Isolerad: Ja