46600 liter tank i Syrafast 904L



467 000 SEK /st exkl moms

Additional information: Manhole approx. 535 x 435 mm; 1 guardrail and 4 load cells are included in the scope of delivery (total height specified includes these parts); The insulation jacket was cut open in places during disassembly (parts of the jacket from the cut areas are still present but loose); some residues of previous content
Volumetric volume (L): 46.600 L

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Pressure in tank: ATM - atmosferic
Max. temperature (°C): 70 °C
Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no

Total discharge: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no

Position of manway: cylinder
Outlet of tank: flange DN80
Agitator: yes
Number of revolutions: 18 / 36
Power: 2.1 / 4.2

Top: 5 mm
Cylinder: 4 mm
Bottom: 4 mm
Internal diameter tank: 3.500 mm
Outer diameter tank: 3.720 mm

Cylinder height: 5.500 mm
Total height of tank: 9.200 mm

SKU: 703247

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer information

Beskrivning av produkt

Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: insulated
Max. arbetstemperatur: 70 °C
Mobil tank: Nej
Övrig information: Food; Manhole diameter: approx. 530 x 430 mm; dimensions as shown in the drawing; we can't give any guarantees about the agitator
Övrig information2: disassembly (parts of the jacket from the cut areas are still present but loose); some residues of previous content; we can't give any guarantees about the agitator
Omrörare: Ja
Total urtappning: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316L (V4A)
Volym i liter: 46600

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Dimensioner av tank

Cylinderhöjd: 5.500 mm
Invändig diameter: 3.500 mm
Total höjd: 8.790 mm
Ytterdiameter: 3.720 mm

Omrörare
Kraft (kW): 2.1 / 4.2
Varvtal: 18 / 36

Tjocklek på tank
Botten: 4 mm
Cylinder: 4 mm
Topp: 5 mm

Mer
Isolerad: Ja