4700 liter tank i Syrafast 316



425 000 SEK /st exkl moms

Additional information: Apparatus was manufactured for a global pharmaceutical company but never put into operation there; diameter of spout (fitting) approx. 44 mm
Volumetric volume (L): 4.700 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 6 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: no
Volume: 117 L
Max Overpressure: 10 Bar

Max onderdruk: 1 Bar
Max. working temperature: 150 °C
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Top: 11,20 mm
Cylinder: 5,50 mm

Bottom: 9,10 mm
Internal diameter tank: 1.600 mm
Outer diameter tank: 1.800 mm
Cylinder height: 1.800 mm
Total height of tank: 3.800 mm

SKU: 441335

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 150 °C
Mobil tank: Nej
Övrig information: Tank was manufactured for a global pharmaceutical company but was never put into operation; Diameter of outlet (fitting) approx. 44 mm; we can’t give any guarantees about the heating/cooling jacket
Övrig information2: jacket
Omrörare: Nej
Övertryck: 6 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 4700

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Dimensioner av tank

Cylinderhöjd: 1.800 mm
Invändig diameter: 1.600 mm
Total höjd: 3.800 mm
Ytterdiameter: 1.800 mm

Tjocklek på tank

Botten: 9,10 mm
Cylinder: 5,50 mm
Topp: 11,20 mm

Mer

Isolerad: Ja