

4700 liter tank i Syrafast 316



415,000,00 kr /st exkl moms

Additional information: Apparatus was manufactured for a global pharmaceutical company but never put into operation there; diameter of spout (fitting) approx. 44 mm

Volumetric volume (L): 4.700 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 6 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: no

Volume: 117 L

Max Overpressure: 10 Bar

Max onderdruk: 1 Bar

Max. working temperature: 150 °C

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Top: 11,20 mm

Cylinder: 5,50 mm

Bottom: 9,10 mm

Internal diameter tank: 1.600 mm

Outer diameter tank: 1.800 mm

Cylinder height: 1.800 mm

Total height of tank: 3.800 mm

SKU: 441335

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: Tank was manufactured for a global pharmaceutical company but was never put into operation; Diameter of outlet (fitting) approx. 44 mm; we can't give any guarantees about the heating/cooling jacket

Övrig information2: jacket

Omrörare: Nej

Övertryck: 6 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 4700

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Cylinderhöjd: 1.800 mm
Invändig diameter: 1.600 mm
Total höjd: 3.800 mm
Ytterdiameter: 1.800 mm

Tjocklek på tank

Botten: 9,10 mm
Cylinder: 5,50 mm
Topp: 11,20 mm

Mer

Isolerad: Ja