

4800 liter tank i Rostfritt 304



333 000 SEK /st exkl moms

Additional information: Cosmetics; 1 flanged outlet reduction (end DN 50 DIN 11851); 1 pallet with accessories is included in the scope of delivery (see photos; these parts were not taken into account in the stated total height)

Volumetric volume (L): 4.800 L

Pressure in tank: ATM - atmospheric

Max. pressure (Bar): 3 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Total discharge: yes
Volume: 220 L
Max Overpressure: 3 Bar

Max onderdruk: 1 Bar
Max. working temperature: 150 °C
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Heat exchanger: RVS 304

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside

Outlet of tank: flange DN100
Number of revolutions: 1.450
Power: 15
Top: 7 mm
Cylinder: 11 mm

Bottom: 8,60 mm
Internal diameter tank: 1.800 mm
Outer diameter tank: 1.950 mm
Cylinder height: 1.400 mm
Total height of tank: 2.900 mm

SKU: 310340

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: single-skin

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: Cosmetics; 1 flanged outlet reduction (end DN 50 DIN 11851); 1 pallet with accessories is included in the scope of delivery (see photos; these parts were not taken into account in the stated total

Övrig information2: height)

Omrörare: Nej

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 4800

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Cylinderhöjd: 1.400 mm
Invändig diameter: 1.800 mm
Total höjd: 2.900 mm
Ytterdiameter: 1.950 mm

Omrörare

Kraft (kW): 15
Varvtal: 1.450

Tjocklek på tank

Botten: 8,60 mm
Cylinder: 11 mm
Topp: 7 mm

Mer

Värmeväxlare: RVS 304
Isolerad: Nej