

48100 liter tank i Syrafast 316



339,000,00 kr /st exkl moms

Additional information: Lösemittel; cylinder manhole diameter: 600 mm

Volumetric volume (L): 48.100 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 1 Bar

Min. pressure (Bar): 0,25 Bar

Max. temperature (°C): 100 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: flange DN100

Top: 10 mm

Cylinder: 6 mm

Bottom: 8 mm

Internal diameter tank: 2.988 mm

Cylinder height: 6.000 mm

Total height of tank: 7.560 mm

SKU: 476395

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nyttillverkad/Begagnad: Begagnad
Arbetsstryck i tank: pressure and vacuum
Konfiguration: single-skin
Max. arbetstemperatur: 100 °C
Mobil tank: Nej
Övrig information: Lösemittel; cylinder manhole diameter: 600 mm
Omrörare: Nej
Övertryck: 1 Bar
Total urtappning: Ja
Undertryck (vakuum): 0,25 Bar
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 48100

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 6.000 mm
Invändig diameter: 2.988 mm
Total höjd: 7.560 mm

Tjocklek på tank

Botten: 8 mm

Cylinder: 6 mm

Topp: 10 mm

Mer

Isolerad: Nej