

4870 liter tank i Syrafast 316



93 000 SEK /st exkl moms

Additional information: chemistry; lower bottoms go deeper than the frame; type plates not available; 1 tank with dent in the double jacket; heating connections cut off; handhole cover is missing

Volumetric volume (L): 4.870 L

Pressure in tank: vacuum

Max. pressure (Bar): 2,50 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 130 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 530 L

Max Overpressure: 2,50 Bar

Max onderdruk: 1 Bar

Max. working temperature: 130 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Position of manway: headside

Outlet of tank: 120

Agitator: yes

Power: 15

Cylinder: 8 mm

Bottom: 8 mm

Internal diameter tank: 1.800 mm

Outer diameter tank: 1.900 mm

Cylinder height: 1.420 mm

Total height of tank: 4.300 mm

SKU: 265897

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 130 °C

Mobil tank: Nej

Övrig information: chemistry; lower bottoms go deeper than the frame; type plates not available; 1 tank with dent in the double jacket; heating connections cut off; handhole cover is missing; we can't give any

Övrig information2: guarantees about the agitator

Omrörare: Ja

Övertryck: 2,50 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 4870

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.420 mm

Invändig diameter: 1.800 mm

Total höjd: 4.300 mm

Ytterdiameter: 1.900 mm

Omrörare

Kraft (kW): 15

Tjocklek på tank

Botten: 8 mm

Cylinder: 8 mm

Mer

Isolerad: Nej