50 liter tank i Syrafast 316



123 000 SEK /st exkl moms

item available on order

Article type: brand new mixing tank - type VC-SLA
Additional information: delivered with food certificate; *article price without agitator; choice of 3 different types of agitators; see options; (The article can also be purchased without options);* Ra=<0.8µm
Volumetric volume (L): 50 L
Max. density P (kg/m³): 1.200
Ra inner weld: 0,80

Finish stainless steel: 2b
Pressure in tank: ATM - atmosferic

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Max. temperature (°C): 80 °C
Min. temperature (°C): -10 °C
Material wet parts: SS AISI 316L (V4A)

Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no

Top type: half hinging lid
With blocking system: yes
Shape of tank: cylindrical
Bottom type: conical 20 °
Total discharge: yes

Fixation points: 3 non adjustable feet
Gasket manway(s): EPDM
Fixation point(s): RVS 304L
Suitable for food industry: yes
Documents included: yes, optional

Technical drawing included: yes
Registration plate on the tank: yes
Flange for agitator: yes
Flange type: Tri-Clamp DN150
CIP spray ball: no, optional

Tank outlet: inside Ø 40 mm
Outlet type: DIN32676 clamp
Total outlet valve: no, optional
Agitator: no, optional
Top: 5 mm

Cylinder: 2,50 mm
Bottom: 2 mm
Internal diameter tank: 406 mm
Distance from outlet to ground: 250 mm
Outer diameter tank: 506 mm

Cylinder height: 375 mm
Total height of tank: 852 mm
Empty weight tank: 35

SKU: 377471

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Nytillverkad
Arbetstryck i tank: ATM – atmospheric
Finish rostfritt stål: 2b
Konfiguration: single-skin
Max. arbetstemperatur: 80 °C
Maximal densitet för produkten: 1200
Min. arbetstemperatur: -10 °C
Mobil tank: Nej
Övrig information: delivered with food certificate; article price without agitator; choice of 3 different types of agitators; see options; (The article can also be purchased without
Övrig information2: options); Ra=<0.8µm
Omrörare: Nej
Ra innersvets: 0,80
Tankens form: cylindrical
Total urtappning: Yes
Typ av botten: conical 20 °
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316L (V4A)
Volym i liter: 50

Utrustning

Fläns för omrörare: Ja
Märkskylt: Ja
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 40 mm
Teknisk ritning finns: Ja
Utloppstyp: DIN32676 clamp

Översikt material

Material: Syrafast 316
Fixeringspunkt(er): RVS 304L

Dimensioner av tank

Cylinderhöjd: 375 mm
Invändig diameter: 406 mm
Mått utlopp till marken: 250 mm
Total höjd: 852 mm
Ytterdiameter: 506 mm

Tjocklek på tank

Botten: 2 mm
Cylinder: 2,50 mm
Topp: 5 mm

Mer

Isolerad: Nej
Vikt: 35