

## 50 liter tank i Syrafast 316



**123 000 SEK /st exkl moms**

item available on order

**Article type:** brand new mixing tank - type VC-SLA

**Additional information:** delivered with food certificate; *article price without agitator*; choice of 3 different types of agitators; see options; (The article can also be purchased without options); Ra=<0.8µm

**Volumetric volume (L):** 50 L

**Max. density P (kg/m<sup>3</sup>):** 1.200

**Ra inner weld:** 0,80

**Finish stainless steel:** 2b



**Pressure in tank:** ATM - atmosferic  
**Max. temperature (°C):** 80 °C  
**Min. temperature (°C):** -10 °C  
**Material wet parts:** SS AISI 316L (V4A)

**Model:** vertical  
**Configuration:** single-skin  
**Heat exchanger:** no  
**Insulation:** no  
**Mobile tank:** no

**Top type:** half hinging lid  
**With blocking system:** yes  
**Shape of tank:** cylindrical  
**Bottom type:** conical 20 °  
**Total discharge:** yes

**Fixation points:** 3 non adjustable feet  
**Gasket manway(s):** EPDM  
**Fixation point(s):** RVS 304L  
**Suitable for food industry:** yes  
**Documents included:** yes, optional

**Technical drawing included:** yes  
**Registration plate on the tank:** yes  
**Flange for agitator:** yes  
**Flange type:** Tri-Clamp DN150  
**CIP spray ball:** no, optional

**Tank outlet:** inside Ø 40 mm  
**Outlet type:** DIN32676 clamp  
**Total outlet valve:** no, optional  
**Agitator:** no, optional  
**Top:** 5 mm

**Cylinder:** 2,50 mm  
**Bottom:** 2 mm  
**Internal diameter tank:** 406 mm  
**Distance from outlet to ground:** 250 mm

**Outer diameter tank:** 506 mm

**Cylinder height:** 375 mm

**Total height of tank:** 852 mm

**Empty weight tank:** 35

**SKU:** 377471

---

Mer information

## Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Nyttillverkad

Arbetstryck i tank: ATM – atmosferic

Finish rostfritt stål: 2b

Konfiguration: single-skin

Max. arbetstemperatur: 80 °C

Maximal densitet för produkten: 1200

Min. arbetstemperatur: -10 °C

Mobil tank: Nej

Övrig information: delivered with food certificate; article price without agitator; choice of 3 different types of agitators; see options; (The article can also be purchased without

Övrig information2: options); Ra=<0.8µm

Omrörare: Nej

Ra innersvets: 0,80

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical 20 °

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316L (V4A)

Volym i liter: 50

## Utrustning

Fläns för omrörare: Ja

Märkskylt: Ja

Livsmedelsklassad: Ja

Tankutlopp: inside Ø 40 mm

Teknisk ritning finns: Ja

Utloppstyp: DIN32676 clamp

## Översikt material

Material: Syrafast 316

Fixeringspunkt(er): RVS 304L



## Dimensioner av tank

Cylinderhöjd: 375 mm

Invändig diameter: 406 mm

Mått utlopp till marken: 250 mm

Total höjd: 852 mm

Ytterdiameter: 506 mm

## Tjocklek på tank

Botten: 2 mm

Cylinder: 2,50 mm

Topp: 5 mm

## Mer

Isolerad: Nej

Vikt: 35