

50 liter tank i Syrafast 316



144,000,00 kr /st exkl moms

item available on order

Article type: brand new mixing tank - type VC-SCA

Additional information: delivered with food certificate; *article price without agitator*; choice of 3 different types of agitators; see options; (The article can also be purchased without options); Ra=<0.8µm

Volumetric volume (L): 50 L

Max. density P (kg/m³): 1.200

Ra inner weld: 0,80

Finish stainless steel: 2b



Pressure in tank: ATM - atmosferic
Max. temperature (°C): 80 °C
Min. temperature (°C): -10 °C
Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: yes

Top type: half hinging lid
With blocking system: yes
Shape of tank: cylindrical
Bottom type: conical 20 °
Total discharge: yes

Fixation points: 4 casters
Spray ball: RVS 316L
Gasket manway(s): EPDM
Valve: RVS 316L
Gasket shut-off valve (mat): EPDM

Fixation point(s): RVS 304
Suitable for food industry: yes
Documents included: yes, optional
Technical drawing included: yes
Registration plate on the tank: yes

Flange for agitator: yes
Flange type: Tri-Clamp DN150
CIP spray ball: no, optional
Tank outlet: inside Ø 40 mm
Outlet type: DIN32676 clamp

Total outlet valve: no, optional
Agitator: no, optional
Top: 5 mm
Cylinder: 2,50 mm



Bottom: 2 mm

Internal diameter tank: 406 mm

Distance from outlet to ground: 250 mm

Outer diameter tank: 506 mm

Cylinder height: 375 mm

Total height of tank: 827 mm

Empty weight tank: 40

SKU: 8834

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Nyttillverkad

Arbetstryck i tank: ATM – atmosferic

Finish rostfritt stål: 2b

Konfiguration: single-skin

Max. arbetstemperatur: 80 °C

Maximal densitet för produkten: 1200

Min. arbetstemperatur: -10 °C

Mobil tank: Ja

Övrig information: delivered with food certificate; article price without agitator; choice of 3 different types of agitators; see options; (The article can also be purchased without options);

Övrig information2: Ra=<0.8µm

Omrörare: Nej

Ra innersvets: 0,80

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical 20 °

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 50

Utrustning

Fläns för omrörare: Ja

Märkskylt: Ja

Livsmedelsklassad: Ja

Tankutlopp: inside Ø 40 mm

Teknisk ritning finns: Ja

Utloppstyp: DIN32676 clamp

Översikt material

Material: Syrafast 316

Fixeringspunkt(er): RVS 304

Dimensioner av tank

Cylinderhöjd: 375 mm

Invändig diameter: 406 mm

Mått utlopp till marken: 250 mm

Total höjd: 827 mm

Ytterdiameter: 506 mm

Tjocklek på tank

Botten: 2 mm

Cylinder: 2,50 mm

Topp: 5 mm

Mer

Isolerad: Nej

Vikt: 40