500 liter tank i Syrafast 316



58 000 SEK /st exkl moms

item available on order

Article type: brand new pressure tank - type BBT-ES-SL
Volumetric volume (L): 500 L
Ra inner weld: 0,80
Pressure in tank: pressure
Max. pressure (Bar): 2 Bar

Max. temperature (°C): 130 °C
Min. temperature (°C): -10 °C
Material wet parts: SS AISI 316L (V4A)
Model: vertical
Configuration: single-skin

Heat exchanger: no
Insulation: no
Mobile tank: no
Top type: dished
Shape of tank: cylindrical

Bottom type: dished
Total discharge: yes
Fixation points: 4 non adjustable feet
Manway(s): RVS 316
Gasket manway(s): EPDM

Valve: RVS 316L
Gasket shut-off valve (mat): EPDM
Fixation point(s): RVS 304
Suitable for food industry: yes
Documents included: yes, optional

Technical drawing included: yes
Registration plate on the tank: yes
Inspection of: TUV
Flange for agitator: no
Number of manways: 1

Position of manway: at the top
Height manhole 1 (mm): 400 mm
CIP spray ball: no, optional
Tank outlet: inside Ø 50 mm
Outlet type: DIN11851 male

Total outlet valve: yes
Agitator: no, optional
Top: 2,50 mm
Cylinder: 2 mm
Bottom: 2,50 mm

Distance from outlet to ground: 202 mm
Outer diameter tank: 1.140 mm
Cylinder height: 200 mm
Total height of tank: 1.054 mm

Empty weight tank: 180

SKU: 381311

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Nytillverkad
Arbetstryck i tank: pressure
Konfiguration: single-skin
Max. arbetstemperatur: 130 °C
Min. arbetstemperatur: -10 °C
Mobil tank: Nej
Omrörare: Nej
Övertryck: 2 Bar
Ra innersvets: 0,80
Tankens form: cylindrical
Total urtappning: Ja
Typ av botten: dished
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316L (V4A)
Volym i liter: 500

Utrustning
Fläns för omrörare: Nej
Märkskylt: Ja
Livsmedelsklassad: Ja
med besiktning av: TUV
Tankutlopp: inside Ø 50 mm
Teknisk ritning finns: Ja
Utloppstyp: DIN11851 male
Utloppsventil: Ja

Översikt material
Material: Syrafast 316
Fixeringspunkt(er): RVS 304

Dimensioner av tank
Cylinderhöjd: 200 mm
Mått utlopp till marken: 202 mm
Total höjd: 1.054 mm
Ytterdiameter: 1.140 mm

Tjocklek på tank
Botten: 2,50 mm
Cylinder: 2 mm
Topp: 2,50 mm

Mer
Isolerad: Nej
Vikt: 180

Rodervägen 57
891 78 Bonässund
info@processoverskott.se