

500 liter tank i Syrafast 316



59,000,00 kr /st exkl moms

Article type: brand new storage tank - type K-SL

Volumetric volume (L): 500 L

Max. density P (kg/m³): 1.200

Ra inner weld: 1,60

Finish stainless steel: 2b

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Top type: conical 15 %

Shape of tank: cylindrical

Bottom type: conical 15 %

Total discharge: yes

Fixation points: 3 adjustable feet

Legs: Set of baseplates and adjusting pieces included

Manway(s): RVS 316

Valve: RVS 316L

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: yes, optional

Technical drawing included: yes

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 400 mm

Hinged lid: yes

CIP spray ball: no

Tank outlet: inside Ø 50 mm

Outlet type: DIN11851

Total outlet valve: no, optional

Adjustable legs: yes

Agitator: no, optional

Top: 2,50 mm

Cylinder: 2 mm

Bottom: 2,50 mm

Distance from outlet to ground: 240 mm

Outer diameter tank: 796 mm

Cylinder height: 1.000 mm

Total height of tank: 1.635 mm

Empty weight tank: 80

SKU: 7079

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: Syrafast 316
Modell: Vertikal
Nyttillverkad/Begagnad: Nyttillverkad
Arbetstryck i tank: ATM – atmosferic
Finish rostfritt stål: 2b
Konfiguration: single-skin
Maximal densitet för produkten: 1200
Mobil tank: Nej
Omrörare: Nej
Ra innersvets: 1,60
Tankens form: cylindrical
Total urtappning: Ja
Typ av botten: conical 15 %
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 500

Utrustning

Fläns för omrörare: Nej
Märkskylt: Ja
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 50 mm
Teknisk ritning finns: Ja
Utloppstyp: DIN11851

Översikt material

Material: Syrafast 316
Fixeringspunkt(er): RVS 304



Dimensioner av tank

Cylinderhöjd: 1.000 mm
Mått utlopp till marken: 240 mm
Total höjd: 1.635 mm
Ytterdiameter: 796 mm

Tjocklek på tank

Botten: 2,50 mm
Cylinder: 2 mm
Topp: 2,50 mm

Mer

Isolerad: Nej
Vikt: 80