500 liter tank i Syrafast 316



PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

58 000 SEK /st exkl moms

Article type: brand new storage tank - type K-SL
Volumetric volume (L): 500 L
Max. density P (kg/m³): 1.200
Ra inner weld: 1,60
Finish stainless steel: 2b

Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Top type: conical 15 %
Shape of tank: cylindrical
Bottom type: conical 15 %

Total discharge: yes
Fixation points: 3 adjustable feet
Legs: Set of baseplates and adjusting pieces included
Manway(s): RVS 316
Valve: RVS 316L

Fixation point(s): RVS 304
Suitable for food industry: yes
Documents included: yes, optional
Technical drawing included: yes
Registration plate on the tank: yes

Flange for agitator: no
Number of manways: 1
Position of manway: at the top
Height manhole 1 (mm): 400 mm
Hinged lid: yes

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

CIP spray ball: no
Tank outlet: inside Ø 50 mm
Outlet type: DIN11851
Total outlet valve: no, optional
Adjustable legs: yes

Agitator: no, optional
Top: 2,50 mm
Cylinder: 2 mm
Bottom: 2,50 mm
Distance from outlet to ground: 240 mm

Outer diameter tank: 796 mm
Cylinder height: 1.000 mm
Total height of tank: 1.635 mm
Empty weight tank: 80

SKU: 375992

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Nytillverkad
Arbetstryck i tank: ATM – atmospheric
Finish rostfritt stål: 2b
Konfiguration: single-skin
Maximal densitet för produkten: 1200
Mobil tank: Nej
Omrörare: Nej
Ra innersvets: 1,60
Tankens form: cylindrical
Total urtappning: Yes
Typ av botten: conical 15 %
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 500

Utrustning

Fläns för omrörare: Nej
Märkskylt: Ja
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 50 mm
Teknisk ritning finns: Ja
Utloppstyp: DIN11851

Översikt material

Material: Syrafast 316
Fixeringspunkt(er): RVS 304

Dimensioner av tank

Cylinderhöjd: 1.000 mm
Mått utlopp till marken: 240 mm
Total höjd: 1.635 mm
Ytterdiameter: 796 mm

Tjocklek på tank

Botten: 2,50 mm
Cylinder: 2 mm
Topp: 2,50 mm

Mer

Isolerad: Nej
Vikt: 80