



500 liter tank i Syrafast 316



Article type: brand new storage tank - type K-SL

Additional information: Ra=<0.8µm

Capacity: 500 L

Maximal density of the product: 1.200

Ra inner weld: 0,80

Finish stainless steel: 2b

Working pressure in tank: ATM - atmosferic

Max. working temperature: 90 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Agitator: yes, optional

Mobile tank: no

Top type: conical 15 °



Shape of tank: cylindrical
Bottom type: conical 15 °
Total discharge: yes
Fixation points: 3 adjustable feet

Legs: Set of baseplates and adjusting pieces included
Manway(s): RVS 316
Gasket manway(s): EPDM
Valve: RVS 316L
Fixation point(s): RVS 304

Suitable for food industry: yes
Documents included: yes, optional
Technical drawing included: yes
Registration plate on the tank: yes
Flange for agitator: no

Number of manways: 1
Position manway: at the top
Manway 1: 400 mm
Hinged lid: yes
Spray ball: no

Tank outlet: inside Ø 50 mm
Outlet type: DIN11851
Total outlet valve: yes, optional
Type shut-off valve: butterfly valve
Adjustable legs: yes

Top: 2,50 mm
Cylinder: 2 mm
Bottom: 2,50 mm
Distance from outlet to ground: 273 mm
Outer diameter tank: 950 mm

Cylinder height: 750 mm
Height of top: 140 mm
Height of bottom: 140 mm
Total height of tank: 1.505 mm
Empty weight tank: 85

SKU: 5774



Additional Information

Volym i liter	500
Nyttillverkad/Begagnad	Nyttillverkad
Livsmedelsklassad	Ja
Modell	Vertikal
Material	Syrafast 316
Omrörare	Nej
Uppvärmning/kylning	Nej
Isolerad	Nej