

## 500 liter tank i Syrafast 316



**137 000 SEK /st exkl moms**

**PROCESSÖVERSKOTT AB**

Rodervägen 57  
891 78 Bonässund  
info@processoverskott.se

Läs våra köpvillkor

## item available on order

**Article type:** brand new mixing tank - type VC-SCA

**Additional information:** example picture; delivered with food certificate; *article price without agitator; choice of 2 different types of agitators; see options; (The article can also be purchased without options);* Ra=<0.8µm

**Volumetric volume (L):** 500 L

**Max. density P (kg/m<sup>3</sup>):** 1.200

**Ra inner weld:** 0,80

**Pressure in tank:** ATM - atmosferic

**Max. temperature (°C):** 80 °C

**Min. temperature (°C):** -10 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** single-skin

**Heat exchanger:** no

**Insulation:** no

**Mobile tank:** yes

**Top type:** half hinging lid °

**Shape of tank:** cylindrical

**Bottom type:** conical 10 °

**Total discharge:** yes

**Fixation points:** 4 casters

**Valve:** RVS 316L

**Fixation point(s):** RVS 304

**Suitable for food industry:** yes

**Documents included:** yes, optional

**Technical drawing included:** yes

**Registration plate on the tank:** yes

**Flange for agitator:** yes

**CIP spray ball:** no, optional

**Tank outlet:** inside Ø 40 mm

**Outlet type:** DIN11851

**Total outlet valve:** no, optional

**Agitator:** no, optional

**Outer diameter tank:** 890 mm  
**Total height of tank:** 1.780 mm  
**Empty weight tank:** 130

**SKU:** 8285

---

Mer information



## Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Nyttillverkad

Arbetstryck i tank: ATM – atmosfäric

Konfiguration: single-skin

Max. arbetstemperatur: 80 °C

Maximal densitet för produkten: 1200

Min. arbetstemperatur: -10 °C

Mobil tank: Ja

Övrig information: example picture; delivered with food certificate; article price without agitator; choice of 2 different types of agitators; see options; (The article can also be purchased without options);

Övrig information2: Ra=<0.8µm

Omrörare: Nej

Ra innersvets: 0,80

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical 10 °

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 500

## Utrustning

Fläns för omrörare: Ja

Märkskylt: Ja

Livsmedelsklassad: Ja

Tankutlopp: inside Ø 40 mm

Teknisk ritning finns: Ja

Utloppstyp: DIN11851

## Översikt material

Material: Syrafast 316

Fixeringspunkt(er): RVS 304

**Dimensioner av tank**

Total höjd: 1.780 mm

Ytterdiameter: 890 mm

**Mer**

Isolerad: Nej

Vikt: 130