

## 500 liter tank i Rostfritt 304



**37 000 SEK /st exkl moms**

**Additional information:** Diameter of hand hole 200 mm; base frame made of stainless steel 304 with upper ring made of Fe; other external parts made of Fe (e.g. heating connections; clamp screws of the upper bottom); double jacket by approx. 600 mm of the cylinder height; 1 small dent in the upper bottom; some residues of previous content

**Volumetric volume (L):** 500 L

**Pressure in tank:** ATM - atmosferic

**Material wet parts:** SS AISI 304 (V2A)

**Model:** vertical

**Configuration:** single jacketed with heat-exchanger

**Heat exchanger:** yes

**Insulation:** no

**Mobile tank:** no

**Total discharge:** yes

**Type HE on the cylinder:** heating/cooling jacket

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** no

**Flange for agitator:** no

**Outlet of tank:** available

**Agitator:** yes

**Number of revolutions:** 705

**Power:** 0,55

**Internal diameter tank:** 740 mm

**Outer diameter tank:** 810 mm

**Cylinder height:** 1.170 mm

**Total height of tank:** 2.150 mm

**SKU:** 277348

Mer information

## Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: single jacketed with heat-exchanger

Mobil tank: Nej

Övrig information: Hand hole diameter 200 mm; Foot frame, Aisi 304 with upper ring made of Fe; other external parts made of Fe (e.g. heating connections; el clamp screws of the upper bottom); double jacket by approx.

Övrig information2: 600 mm of the cylinder height; 1 small dent in the upper bottom ; some residues of previous content; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 500

## Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Teknisk ritning finns: Nej

## Översikt material

Material: Rostfritt 304

## Dimensioner av tank

Cylinderhöjd: 1.170 mm

Invändig diameter: 740 mm

Total höjd: 2.150 mm

Ytterdiameter: 810 mm

**Omrörare**

Kraft (kW): 0,55

Varvtal: 705

**Mer**

Isolerad: Nej