500 liter tank i Rostfritt 304



37 000 SEK /st exkl moms

Additional information: Diameter of hand hole 200 mm; base frame made of stainless steel 304 with upper ring made of Fe; other external parts made of Fe (e.g. heating connections; clamp screws of the upper bottom); double jacket by approx. 600 mm of the cylinder height; 1 small dent in the upper bottom; some residues of previous content
Volumetric volume (L): 500 L

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)
Model: vertical

Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no
Total discharge: yes

Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no

Outlet of tank: available
Agitator: yes
Number of revolutions: 705
Power: 0,55
Internal diameter tank: 740 mm

Outer diameter tank: 810 mm
Cylinder height: 1.170 mm
Total height of tank: 2.150 mm

SKU: 401414

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: single jacketed with heat-exchanger
Mobil tank: Nej
Övrig information: Hand hole diameter 200 mm; Foot frame, Aisi 304 with upper ring made of Fe; other external parts made of Fe (e.g. heating connections; el clamp screws of the upper bottom); double jacket by approx.
Övrig information2: 600 mm of the cylinder height; 1 small dent in the upper bottom ; some residues of previous content; we can’t give any guarantees about the agitator
Omrörare: Ja
Total urtappning: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 500

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 1.170 mm
Invändig diameter: 740 mm
Total höjd: 2.150 mm
Ytterdiameter: 810 mm

Omrörare
Kraft (kW): 0,55
Varvtal: 705

Mer
Isolerad: Nej