

500 liter tank i Syrafast 316



80,000,00 kr /st exkl moms

Additional information: Acids and alkalis; 3 support brackets, Aisi 304; 1 hand hole DN 200 in the upper bottom; Metallic discolouration inside

Volumetric volume (L): 500 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 156 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 20 L

Max Overpressure: 6 Bar

Max. working temperature: 156 °C

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: 48

Cylinder: 5 mm

Bottom: 5 mm

Internal diameter tank: 800 mm

Outer diameter tank: 1.000 mm

Total height of tank: 1.600 mm

Empty weight tank: 650

SKU: 298898

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 156 °C

Mobil tank: Nej

Övrig information: Acids and alkalis; 3 support brackets, Aisi 304; 1 hand hole DN 200 in the upper bottom; Metallic discolouration inside; we can't give any guarantees about the heating/cooling jacket

Omrörare: Nej

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 500

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Invändig diameter: 800 mm

Total höjd: 1.600 mm

Ytterdiameter: 1.000 mm

Tjocklek på tank

Botten: 5 mm

Cylinder: 5 mm

Mer

Isolerad: Ja

Vikt: 650