500 liter tank i Syrafast 316



32 000 SEK /st exkl moms

Article type: second-hand transport tank
Volumetric volume (L): 500 L
Pressure in tank: pressure
Max. pressure (Bar): 0,25 Bar
Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Top type: conical
Shape of tank: square
Bottom type: flat sloping
Total discharge: yes
Fixation points: 4 non adjustable feet

Suitable for food industry: no
Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no

Number of manways: 1
Position of manway: at the top
Height manhole 1 (mm): 400 mm
Tank outlet: inside Ø 51 mm
Outlet type: SMS 51

Total outlet valve: yes
Agitator: no, optional
Distance from outlet to ground: 100 mm
Cylinder height: 240 mm
Total height of tank: 1.000 mm

Total outer width: 1.150 mm
Total outer length: 1.150 mm
Empty weight tank: 180

SKU: 387542

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure
Konfiguration: single-skin
Mobil tank: Nej
Omrörare: Nej
Övertryck: 0,25 Bar
Tankens form: square
Total urtappning: Yes
Typ av botten: flat sloping
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 500

Utrustning

Dokument finns: Nei, det er det ikke.
Fläns för omrörare: Nej
Märkskylt: Nej
Tankutlopp: inside Ø 51 mm
Teknisk ritning finns: Nej
Utloppstyp: SMS 51
Utloppsventil: Ja

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 240 mm
Mått utlopp till marken: 100 mm
Total höjd: 1.000 mm

Mer
Isolerad: Nej
Vikt: 180

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se