500 liter tank i Syrafast 316



92 000 SEK /st exkl moms

Additional information: An inner double jacket was subsequently welded into the vessel by the previous operator, which reduced the volume indicated on the type plate to approx. 500 liters (see photos); unfortunately, we do not know to what extent the pressure and temperature specifications on the type plate are still valid as a result; total inner diameter of the tank approx. 900 mm, in the area of the inner double jacket approx. 760 mm; 1 hand hole diameter 150 mm in the upper bottom; outlet fitting no longer present;

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

pipe end cut flush
Volumetric volume (L): 500 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 316 (V4A)
Model: vertical

Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no
Total discharge: yes

Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no

Outlet of tank: 42
Agitator: yes
Number of revolutions: 50 - 480
Outer diameter tank: 1.000 mm
Total height of tank: 2.300 mm

SKU: 404579

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: insulated with heat-exchanger
Mobil tank: Nej
Övrig information: An internal double jacket was subsequently welded into the tank by the previous operator, which reduces the volume specified on the type plate to approx. 500 liters (see photos); Unfortunately, we
Övrig information2:
Omrörare: Ja
Total urtappning: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 500

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Total höjd: 2.300 mm
Ytterdiameter: 1.000 mm

Omrörare

Varvtal: 50 – 480

Mer
Isolerad: Ja