5000 liter tank i Rostfritt 304



91 000 SEK /st exkl moms

Additional information: Bottom cover of the isomantle partly made of Fe (see photos); 1 strong dent in the isomantle
Volumetric volume (L): 5.000 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Model: vertical

Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no
Total discharge: yes

Type HE on the cylinder: half pipe welded onto the outside of the innertank
Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no

Position of manway: headside
Outlet of tank: available
Agitator: yes
Number of revolutions: 6.8 / 14
Power: 2.6 / 4.4

Internal diameter tank: 1.880 mm
Outer diameter tank: 2.030 mm
Cylinder height: 1.850 mm
Total height of tank: 3.700 mm

SKU: 398084

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: isolert med varmeveksler
Mobil tank: Nej
Övrig information: Dairy; Insulation cover of the lower bottom partly made of Fe (see photos); 1 strong dent in the insulation jacket; we can't give any guarantees about the heating/cooling jacket; we can't give any
Övrig information2: guarantees about the agitator
Omrörare: Ja
Total urtappning: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 5000

Utrustning

Dokument finns: Nei, det er det ikke.
Fläns för omrörare: Nej
Märkskylt: Nej
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 1.850 mm
Invändig diameter: 1.880 mm
Total höjd: 3.700 mm
Ytterdiameter: 2.030 mm

Omrörare
Kraft (kW): 2.6 / 4.4
Varvtal: 6.8 / 14

Mer
Isolerad: Ja