5000 liter tank i Rostfritt 304

96 000 SEK /st exkl moms

Additional information: 1 former opening in the upper bottom was welded shut by the previous operator (see photos); dents at the insulation jacket
Volumetric volume (L): 5.000 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)
Model: vertical

Configuration: insulated with heat-exchanger
Heat exchanger: yes
Insulation: yes
Mobile tank: no
Total discharge: yes

Type HE on the bottom: half pipe welded onto the outside of the innertank
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Documents included: no
Technical drawing included: no
Registration plate on the tank: no

Flange for agitator: no
Position of manway: in the bottom
Outlet of tank: 90
Agitator: yes
Number of revolutions: 23,50

Power: 1,50
Internal diameter tank: 1.900 mm
Outer diameter tank: 2.040 mm
Cylinder height: 1.800 mm

Total height of tank: 3.400 mm

Empty weight tank: 1.050

SKU: 407789

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: insulated with heat-exchanger
Mobil tank: Nej
Övrig information: 1 former opening in the upper bottom was welded shut by the previous operator (see photos); dents at the insulation jacket; we can't give any guarantees about the heating/cooling jacket; we can't
Övrig information2: give any guarantees about the agitator
Omrörare: Ja
Total urtappning: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 5000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Teknisk ritning finns: Nej

Översikt material
Material: Rostfritt 304

Dimensioner av tank
Cylinderhöjd: 1.800 mm
Invändig diameter: 1.900 mm
Total höjd: 3.400 mm
Ytterdiameter: 2.040 mm

Omrörare
Kraft (kW): 1,50
Varvtal: 23,50

Mer
Isolerad: Ja
Vikt: 1.050