

5000 liter tank i Rostfritt 304



95 000 SEK /st exkl moms

Additional information: 1 former opening in the upper bottom was welded shut by the previous operator (see photos); dents at the insulation jacket

Volumetric volume (L): 5.000 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: 90

Agitator: yes

Number of revolutions: 23,50

Power: 1,50

Internal diameter tank: 1.900 mm

Outer diameter tank: 2.040 mm

Cylinder height: 1.800 mm

Total height of tank: 3.400 mm

Empty weight tank: 1.050

SKU: 283756

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Mobil tank: Nej

Övrig information: 1 former opening in the upper bottom was welded shut by the previous operator (see photos); dents at the insulation jacket; we can't give any guarantees about the heating/cooling jacket; we can't

Övrig information2: give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 5000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 1.800 mm
Invändig diameter: 1.900 mm
Total höjd: 3.400 mm
Ytterdiameter: 2.040 mm

Omrörare

Kraft (kW): 1,50
Varvtal: 23,50

Mer

Isolerad: Ja
Vikt: 1.050