

5000 liter tank i Rostfritt 304



98,000,00 kr /st exkl moms

Additional information: Agriculture; Sheet metal cutout in the insulation jacket of the lower floor (underneath Fe plate); bump at the insulation jacket; scratches inside; Functionality of the double jacket not checked

Volumetric volume (L): 5.000 L

Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)
Model: vertical

Configuration: insulated with heat-exchanger
Heat exchanger: yes
Insulation: yes
Mobile tank: no
Total discharge: yes

Type HE on the cylinder: half pipe welded onto the outside of the innertank
Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no

Position of manway: headside
Outlet of tank: DN80 DIN 11851
Agitator: yes
Number of revolutions: 6.8 / 14
Power: 2.6 / 4.4

Internal diameter tank: 1.900 mm
Outer diameter tank: 2.050 mm
Cylinder height: 1.800 mm
Total height of tank: 3.650 mm

SKU: 284248

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Mobil tank: Nej

Övrig information: Agriculture; Sheet metal cutout in the insulation jacket of the lower floor (underneath Fe plate); bump at the insulation jacket;scratches inside;Functionality of the double jacket not checked; we

Övrig information2: can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 5000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 1.800 mm

Invändig diameter: 1.900 mm

Total höjd: 3.650 mm

Ytterdiameter: 2.050 mm



Omrörare

Kraft (kW): 2.6 / 4.4

Varvtal: 6.8 / 14

Mer

Isolerad: Ja