

5000 liter tank i Rostfritt 304



113 000 SEK /st exkl moms

Additional information: Food industry; Double jacket, possibly with a trickle ring (in this case, the double jacket could only be filled in the upper cylinder connection); Manhole diameter approx. 410 mm; Devices for accommodating load cells under the base plates (the load cells themselves are no longer available)

Volumetric volume (L): 5.000 L

Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)
Model: vertical

Configuration: single jacketed with heat-exchanger
Heat exchanger: yes
Insulation: no
Mobile tank: no
Total discharge: yes

Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no
Registration plate on the tank: no

Flange for agitator: no
Position of manway: in the bottom
Outlet of tank: 48
Agitator: yes
Number of revolutions: 24.5 / 49

Power: 2.2 / 3.7
Internal diameter tank: 1.790 mm
Outer diameter tank: 1.900 mm
Cylinder height: 1.950 mm
Total height of tank: 4.000 mm

SKU: 290822

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: single jacketed with heat-exchanger

Mobil tank: Nej

Övrig information: Food industry; Double jacket, possibly with a trickle ring (in this case, the double jacket could only be filled in the upper cylinder connection); Manhole diameter approx. 410 mm; Devices for

Övrig information2: accommodating load cells under the base plates (the load cells themselves are no longer available); we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 5000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 1.950 mm

Invändig diameter: 1.790 mm

Total höjd: 4.000 mm

Ytterdiameter: 1.900 mm



Omrörare

Kraft (kW): 2.2 / 3.7

Varvtal: 24.5 / 49

Mer

Isolerad: Nej