5000 liter tank i Rostfritt 304



120 000 SEK /st exkl moms

Article type: second-hand mixing tank
Additional information: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator
Volumetric volume (L): 5.000 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)

Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes
Insulation: yes

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mobile tank: no

Top type: conical
Shape of tank: cylindrical
Bottom type: conical
Bottom outlet: yes
Total discharge: yes

Fixation points: 3 adjustable feet
Type of HE on the cylinder: half pipe welded onto the outside of the innertank
Position HE: the complet cilinder
Type of HE on the bottom: half pipe welded onto the outside of the innertank
Manway(s): RVS 304

Gasket manway(s): unknown
Fixation point(s): RVS 304
Suitable for food industry: yes
Documents included: no
Technical drawing included: no

Registration plate on the tank: no
Flange for agitator: no
Number of manways: 1
Position of manway: at the top
Hinged lid: yes

Tank outlet: inside Ø 60 mm
Agitator: yes
Agitator type: propeller agitator
Power: 1,20
Voltage: 400 V - three-phase

Current: 3,10
Distance from outlet to ground: 600 mm
Outer diameter tank: 2.000 mm
Cylinder height: 2.245 mm
Total height of tank: 3.800 mm

Empty weight tank: 1.050

SKU: 416963

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmospheric
Konfiguration: insulated with heat-exchanger
Mobil tank: Nej
Övrig information: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator
Omrörare: Ja
Tankens form: cylindrical
Total urtappning: Yes
Typ av botten: conical
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 5000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 60 mm
Teknisk ritning finns: Nej

Översikt material
Material: Rostfritt 304
Fixeringspunkt(er): RVS 304

Dimensioner av tank
Cylinderhöjd: 2.245 mm
Mått utlopp till marken: 600 mm
Total höjd: 3.800 mm
Ytterdiameter: 2.000 mm

Värmeväxlare
Position värmeväxlare: the complet cilinder
Typ av värmeväxlare på cylinder: half pipe welded onto the outside of the innertank
Typ av värmeväxlare på botten: half pipe welded onto the outside of the innertank

Omrörare
Kraft (kW): 1,20
Typ av omrörare: propeller agitator
Spänning (Volt): 400 V – three-phase

Mer
Isolerad: Ja
Vikt: 1.050