

5000 liter tank i Rostfritt 304



133 000 SEK /st exkl moms

Additional information: Unfortunately, the nameplate does not include pressure and temperature specifications for the heating coil or the Thermoplate.

Volumetric volume (L): 5.000 L

Pressure in tank: ATM - atmospheric

Max. temperature (°C): 80 °C



Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: DN50 DIN 11851

Agitator: yes

Number of revolutions: 125

Power: 0,75

Internal diameter tank: 1.990 mm

Outer diameter tank: 2.020 mm

Cylinder height: 1.600 mm

Total height of tank: 3.100 mm

SKU: 707743

Mer information



Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmospheric

Konfiguration: single-skin

Max. arbetstemperatur: 80 °C

Mobil tank: Nej

Övrig information: Unfortunately, the nameplate does not include pressure and temperature specifications for the heating coil or the Thermoplate.; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Yes

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 5000

Utrustning

Dokument finns: Nei, det er det ikke.

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 1.600 mm

Invändig diameter: 1.990 mm

Total höjd: 3.100 mm

Ytterdiameter: 2.020 mm

**Omrörare**

Kraft (kW): 0,75

Varvtal: 125

Mer

Isolerad: Nej