

## 5000 liter tank i Rostfritt 304



**132 000 SEK /st exkl moms**

**Additional information:** Dairy (cheese production); Double jacket with trickle ring - only suitable for cooling (pressure of 3.5 bar for cooling stated in the drawing - not stated on the name plate); Rectangular opening on top of the tank; some residues of previous content

**Volumetric volume (L):** 5.000 L

**Pressure in tank:** ATM - atmosferic  
**Material wet parts:** SS AISI 304 (V2A)  
**Model:** horizontal

**Configuration:** single jacketed with heat-exchanger  
**Heat exchanger:** yes  
**Insulation:** no  
**Mobile tank:** no  
**Total discharge:** yes

**Type HE on the cylinder:** heating/cooling jacket  
**Documents included:** no  
**Technical drawing included:** no  
**Registration plate on the tank:** yes  
**Flange for agitator:** no

**Outlet of tank:** flange DN100  
**Agitator:** yes  
**Cylinder:** 5 mm  
**Bottom:** 4 mm  
**Internal diameter tank:** 1.600 mm

**Outer diameter tank:** 1.700 mm  
**Total height of tank:** 2.250 mm  
**Total outer length:** 4.250 mm

**SKU:** 310966

Mer information

## Beskrivning av produkt

Material: Rostfritt 304

Modell: Horisontell

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: single jacketed with heat-exchanger

Mobil tank: Nej

Övrig information: Dairy (cheese production); Double jacket with trickle ring – only suitable for cooling (pressure of 3.5 bar for cooling stated in the drawing – not stated on the name plate);

Rectangular opening on

Övrig information2: top of the tank; some residues of previous content; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 5000

## Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

## Översikt material

Material: Rostfritt 304

## Dimensioner av tank

Invändig diameter: 1.600 mm

Total höjd: 2.250 mm

Ytterdiameter: 1.700 mm

**Tjocklek på tank**

Botten: 4 mm

Cylinder: 5 mm

**Mer**

Isolerad: Nej