

5000 liter tank i Rostfritt 304



113,000,00 kr /st exkl moms

Additional information: chemistry; 2 tanks (6169-3+5) with broken intermediate flange at the gear; some residues of previous content

Volumetric volume (L): 5.000 L

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 60 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 98 L

Max Overpressure: 10 Bar

Max. working temperature: 60 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: flange DN80

Agitator: yes

Number of revolutions: 26 - 101

Power: 6,80

Top: 9 mm

Cylinder: 6 mm

Bottom: 5,40 mm

Internal diameter tank: 1.800 mm

Cylinder height: 1.750 mm

Total height of tank: 4.200 mm

SKU: 267427

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosfäric

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 60 °C

Mobil tank: Nej

Övrig information: chemistry; 2 tanks (6169-3+5) with broken intermediate flange at the gear; some residues of previous content; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 5000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 1.750 mm

Invändig diameter: 1.800 mm

Total höjd: 4.200 mm



Omrörare

Kraft (kW): 6,80
Varvtal: 26 – 101

Tjocklek på tank

Botten: 5,40 mm
Cylinder: 6 mm
Topp: 9 mm

Mer

Värmeväxlare: RVS 304
Isolerad: Nej