5000 liter tank i Rostfritt 304



113 000 SEK /st exkl moms

Additional information: chemistry; 2 vessels (6169-3+5) with broken intermediate flange on gearbox; some residues of previous content
Volumetric volume (L): 5.000 L
Pressure in tank: pressure
Max. temperature (°C): 60 °C
Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mobile tank: no

Total discharge: yes
Volume: 98 L
Max Overpressure: 10 Bar
Max. working temperature: 60 °C
Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank
Heat exchanger: RVS 316
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes

Flange for agitator: no
Position of manway: headside
Outlet of tank: flange DN80
Agitator: yes
Number of revolutions: 26 - 101

Power: 6,80
Top: 9 mm
Cylinder: 6 mm
Bottom: 5,40 mm
Internal diameter tank: 1.800 mm

Cylinder height: 1.750 mm
Total height of tank: 4.200 mm

SKU: 391541

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: single jacketed with heat-exchanger
Max. arbetstemperatur: 60 °C
Mobil tank: Nej
Övrig information: chemistry; 2 tanks (6169-3+5) with broken intermediate flange at the gear; some residues of previous content; we can't give any guarantees about the agitator
Omrörare: Ja
Total urtappning: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 5000

Utrustning

Dokument finns: Nei, det er det ikke.
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 1.750 mm
Invändig diameter: 1.800 mm
Total höjd: 4.200 mm

Omrörare
Kraft (kW): 6,80
Varvtal: 26 – 101

Tjocklek på tank
Botten: 5,40 mm
Cylinder: 6 mm
Topp: 9 mm

Mer
Värmeväxlare: RVS 304
Isolerad: Nej