

5000 liter tank i Rostfritt 304



59,000,00 kr /st exkl moms

Article type: second-hand pressure tank

Volumetric volume (L): 5.000 L

Pressure in tank: pressure

Max. pressure (Bar): 0,40 Bar

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Top type: dished

Shape of tank: cylindrical

Bottom type: dished

Total discharge: yes

Fixation points: 4 adjustable feet

Manway(s): RVS 304

Gasket manway(s): unknown

Valve: RVS 304

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: cylinder

Height manhole 1 (mm): 350 mm x H 450 mm

Tank outlet: inside Ø 65 mm

Agitator: no, optional

Top: 3 mm

Cylinder: 3 mm

Bottom: 3 mm

Distance from outlet to ground: 270 mm

Outer diameter tank: 1.700 mm

Cylinder height: 2.100 mm

Total height of tank: 3.200 mm

Empty weight tank: 1.000

SKU: 437126

Mer information
