

5000 liter tank i Rostfritt 304



122,000,00 kr /st exkl moms

Article type: second-hand mixing tank

Additional information: we can't give any guarantees about the agitator

Volumetric volume (L): 5.000 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Top type: conical

Shape of tank: cylindrical

Bottom type: conical

Total discharge: yes

Fixation points: 4 adjustable feet

Outer jacket (ornamental wall): RVS 304

Manway(s): RVS 304

Gasket manway(s): unknown

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Agitator: yes

Agitator type: tripod

Position engine: at the top

Number of revolutions: 45

Power: 1,10

Voltage: three-phase

Internal diameter tank: 2.100 mm

Outer diameter tank: 2.200 mm

Total height of tank: 3.100 mm

SKU: 450341

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: insulated

Mobil tank: Nej

Övrig information: we can't give any guarantees about the agitator

Omrörare: Ja

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 5000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Livsmedelsklassad: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Fixeringspunkt(er): RVS 304

Ytterbeklädnad: RVS 304

Dimensioner av tank

Invändig diameter: 2.100 mm

Total höjd: 3.100 mm

Ytterdiameter: 2.200 mm

Omrörare

Kraft (kW): 1,10

Position motor: at the top

Typ av omrörare: tripod

Varvtal: 45

Spänning (Volt): three-phase

Mer

Isolerad: Ja