5000 liter tank i Rostfritt 304



206 000 SEK /st exkl moms

Additional information: Food industry; Heating coil around the outside of the lower cylinder area; 3 of the feet are fitted with load cells (no guarantee of functionality); the load cell is missing on one foot; some residues of previous content
Volumetric volume (L): 5.000 L
Pressure in tank: pressure

Material wet parts: SS AISI 316 (V4A)
Model: vertical

Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no
Total discharge: yes

Volume: 102 L
Max Overpressure: 4 Bar
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Outlet of tank: 48
Agitator: yes

Internal diameter tank: 1.600 mm
Outer diameter tank: 1.870 mm
Cylinder height: 2.150 mm
Total height of tank: 4.100 mm

SKU: 456050

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: insulated with heat-exchanger
Mobil tank: Nej
Övrig information: Food industry; Heating coil outside around the lower cylinder area; 3 of the feet are equipped with load cells (no guarantee of functionality); one foot is missing the load cell ; some residues of
Övrig information2: previous content; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator
Omrörare: Ja
Total urtappning: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 5000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 2.150 mm
Invändig diameter: 1.600 mm
Total höjd: 4.100 mm
Ytterdiameter: 1.870 mm

Mer
Isolerad: Ja