

5000 liter tank i Rostfritt 304



35,000,00 kr /st exkl moms

Additional information: dairy; dents in the inner cylinder (overpressure double jacket); insulation jacket partly sliced and new tack welded; bump at the insulation jacket

Volumetric volume (L): 5.000 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: flange DN65

Agitator: yes

Power: 0.5 / 0.75

Internal diameter tank: 2.000 mm

Outer diameter tank: 2.150 mm

Cylinder height: 1.500 mm

Total height of tank: 3.000 mm

Empty weight tank: 860

SKU: 268801

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: insulated

Mobil tank: Nej

Övrig information: dairy; dents in the inner cylinder (overpressure double jacket); insulation jacket partly sliced and new tack welded; bump at the insulation jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 5000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 1.500 mm

Invändig diameter: 2.000 mm

Total höjd: 3.000 mm

Ytterdiameter: 2.150 mm

Omrörare

Kraft (kW): 0.5 / 0.75

Mer

Isolerad: Ja

Vikt: 860