

5000 liter tank i Rostfritt 304



82 000 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: heating mantle for "pressureless" bain-marie heating, 1 of the 2 tanks is missing 2 regulating feet, please look carefully at the photos; we can't give any guarantees about the agitator

Volumetric volume (L): 5.000 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Top type: conical

Shape of tank: cylindrical

Bottom type: conical

Total discharge: yes

Fixation points: 4 adjustable feet

Heat exchanger: RVS 304

Manway(s): RVS 304

Gasket manway(s): unknown

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 400 mm

Tank outlet: inside Ø 50 mm

Agitator: yes

Agitator type: gate

Position engine: at the top

Power: 1,50

Voltage: three-phase

Internal diameter tank: 1.800 mm

Distance from outlet to ground: 350 mm

Outer diameter tank: 1.900 mm

Cylinder height: 2.000 mm

Total height of tank: 3.500 mm

Empty weight tank: 750

SKU: 456158

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: single jacketed with heat-exchanger

Mobil tank: Nej

Övrig information: heating mantle for "pressureless" bain-marie heating, 1 of the 2 tanks is missing 2 regulating feet, please look carefully at the photos; we can't give any guarantees about the agitator

Omrörare: Ja

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 5000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Livsmedelsklassad: Ja

Tankutlopp: inside Ø 50 mm

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Fixeringspunkt(er): RVS 304

Dimensioner av tank

Cylinderhöjd: 2.000 mm

Invändig diameter: 1.800 mm

Mått utlopp till marken: 350 mm

Total höjd: 3.500 mm

Ytterdiameter: 1.900 mm

Omrörare

Kraft (kW): 1,50

Position motor: at the top

Typ av omrörare: gate

Spänning (Volt): three-phase

Mer

Värmeväxlare: RVS 304

Isolerad: Nej

Vikt: 750