

5000 liter tank i Syrafast 316



105 000 SEK /st exkl moms

Additional information: Food industry; 1 dent in the inner tank (overpressure of the no longer functional heating jacket; see photos); insulation jacket with smaller dents and partially detached plates; tank with adhesions inside; Devices for load cells under the feet (3 loose load cells are included in the scope of delivery; these were not taken into account when specifying the total height)

Volumetric volume (L): 5.000 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 316 (V4A)
Model: vertical

Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no
Total discharge: yes

Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no
Position of manway: headside

Outlet of tank: 48
Agitator: yes
Number of revolutions: 450 / 965
Power: 1.1 / 4.4
Internal diameter tank: 1.790 mm

Outer diameter tank: 1.900 mm
Cylinder height: 2.100 mm
Total height of tank: 4.150 mm

SKU: N/A

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: insulated

Mobil tank: Nej

Övrig information: Food industry; 1 dent in the inner tank (overpressure of the no longer functional heating jacket; see photos); insulation jacket with smaller dents and partially detached plates; tank with adhesions

Övrig information2:

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 5000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 2.100 mm

Invändig diameter: 1.790 mm

Total höjd: 4.150 mm

Ytterdiameter: 1.900 mm



Omrörare

Kraft (kW): 1.1 / 4.4

Varvtal: 450 / 965

Mer

Isolerad: Ja