

5000 liter tank i Syrafast 316



126,000,00 kr /st exkl moms

Additional information: Food industry; Heating/cooling jacket can also be operated at 3 bar and 143°C (see photo on rating plate); minor dents in the insulating jacket; sheet metal cuts in the insulating jacket (especially in the lower base); some residues of previous content

Volumetric volume (L): 5.000 L

Pressure in tank: ATM - atmosferic
Max. temperature (°C): 100 °C
Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes
Insulation: yes
Mobile tank: no

Total discharge: yes
Volume: 58 L
Max Overpressure: 4 Bar
Max. working temperature: 100 °C
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: yes
Position of manway: headside
Outlet of tank: 50

Power: 1,10
Internal diameter tank: 1.690 mm
Outer diameter tank: 1.830 mm
Cylinder height: 2.100 mm
Total height of tank: 3.300 mm

SKU: 564049

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosfäric

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 100 °C

Mobil tank: Nej

Övrig information: Food industry; Heating/cooling jacket can also be operated at 3 bar and 143°C (see photo on rating plate); minor dents in the insulating jacket; sheet metal cuts in the insulating jacket (especially

Övrig information2: in the lower base); some residues of previous content; we can't give any guarantees about the heating/cooling jacket

Omrörare: Nej

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 5000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Ja

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 2.100 mm

Invändig diameter: 1.690 mm

Total höjd: 3.300 mm

Ytterdiameter: 1.830 mm

Omrörare

Kraft (kW): 1,10

Mer

Isolerad: Ja
