

## 5000 liter tank i Syrafast 316



**126 000 SEK /st exkl moms**

**Additional information:** Food industry; Heating/cooling jacket can also be operated at 3 bar and 143°C (see photo on rating plate); minor dents in the insulating jacket; sheet metal cuts in the insulating jacket (especially in the lower base); some residues of previous content

**Volumetric volume (L):** 5.000 L

**Pressure in tank:** ATM - atmosferic  
**Max. temperature (°C):** 100 °C  
**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical  
**Configuration:** insulated  
**Heat exchanger:** no  
**Insulation:** yes  
**Mobile tank:** no

**Total discharge:** yes  
**Volume:** 58 L  
**Max Overpressure:** 4 Bar  
**Max. working temperature:** 100 °C  
**Documents included:** no

**Technical drawing included:** no  
**Registration plate on the tank:** yes  
**Flange for agitator:** yes  
**Position of manway:** headside  
**Outlet of tank:** 50

**Power:** 1,10  
**Internal diameter tank:** 1.690 mm  
**Outer diameter tank:** 1.830 mm  
**Cylinder height:** 2.100 mm  
**Total height of tank:** 3.300 mm

**SKU:** 564049

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosfäric

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 100 °C

Mobil tank: Nej

Övrig information: Food industry; Heating/cooling jacket can also be operated at 3 bar and 143°C (see photo on rating plate); minor dents in the insulating jacket; sheet metal cuts in the insulating jacket (especially

Övrig information2: in the lower base); some residues of previous content; we can't give any guarantees about the heating/cooling jacket

Omrörare: Nej

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 5000

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Ja

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Syrafast 316

### Dimensioner av tank

Cylinderhöjd: 2.100 mm

Invändig diameter: 1.690 mm

Total höjd: 3.300 mm

Ytterdiameter: 1.830 mm

**Omrörare**

Kraft (kW): 1,10

**Mer**

Isolerad: Ja

---