5000 liter tank i Syrafast 316



304 000 SEK /st exkl moms

Article type: second-hand pressure tank
Additional information: PED file on demand; the tank has never been used
Volumetric volume (L): 5.000 L
Max. density P (kg/m³): 1.800
Pressure in tank: pressure

Max. pressure (Bar): 6 Bar
Min. pressure (Bar): -1 Bar
Max. temperature (°C): 150 °C
Material wet parts: SS AISI 316L (V4A)
Model: vertical

Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no
Top type: dished

Shape of tank: cylindrical
Bottom type: dished
Total discharge: yes
Fixation points: 4 non adjustable feet
Insulation material: Rockwool

Outer jacket (ornamental wall): RVS 304L
Manway(s): RVS 316
Gasket manway(s): unknown
Fixation point(s): RVS 304L
Suitable for food industry: yes

Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no
Number of manways: 1

Position of manway: at the top
Height manhole 1 (mm): 700 mm
Tank outlet: outside Ø 100 mm
Agitator: no, optional
Top: 15 mm

Cylinder: 6 mm
Bottom: 6 mm
Cylinder: 2
Insulation body: yes
Bottom: 2

Insulation bottom/sides: yes
finish of the outer jacket: welded
Insulation thickness: 60
Internal diameter tank: 1.750 mm

Distance from outlet to ground: 1.100 mm

Outer diameter tank: 1.890 mm
Cylinder height: 2.000 mm
Total height of tank: 4.450 mm
Empty weight tank: 1.800

SKU: 456398

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure
Konfiguration: insulated
Max. arbetstemperatur: 150 °C
Maximal densitet för produkten: 1800
Mobil tank: Nej
Övrig information: PED file on demand; the tank has never been used
Omrörare: Nej
Övertryck: 6 Bar
Tankens form: cylindrical
Total urtappning: Ja
Typ av botten: dished
Undertryck (vakuum): -1 Bar
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316L (V4A)
Volym i liter: 5000

Utrustning

Dokument finns: Nei, det er det ikke.
Fläns för omrörare: Nej
Märkskylt: Nej
Livsmedelsklassad: Ja
Tankutlopp: outside Ø 100 mm
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316
Fixeringspunkt(er): RVS 304L
Isoleringsmaterial: Rockwool
Ytterbeklädnad: RVS 304L

Dimensioner av tank

Cylinderhöjd: 2.000 mm
Invändig diameter: 1.750 mm
Mått utlopp till marken: 1.100 mm
Total höjd: 4.450 mm
Ytterdiameter: 1.890 mm

Tjocklek på tank

Botten: 6 mm
Cylinder: 6 mm
Topp: 15 mm

Tjocklek på ytterbeklädnad och isolering

Finish utvändig mantel: welded
Isolering botten/gavlar: Ja
Isolering mantel: Ja
Isoleringsmaterial: Rockwool

Mer

Cylinder OW: 2
Botten OW: 2
Isoleringstjocklek OW: 60
Isolerad: Ja
Vikt: 1.800