5000 liter tank i Syrafast 316



156 000 SEK /st exkl moms

Additional information: Upper bottom made of stainless steel 304 (1.4301); 4 claws made of Fe; Slight material damage inside the vessel; some residues of previous content; motor-/gear is missing
Volumetric volume (L): 5.000 L
Pressure in tank: pressure
Max. pressure (Bar): 3,20 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 3,20 Bar

Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no

Mobile tank: no
Total discharge: yes
Max Overpressure: 16 Bar
Type HE on the bottom: half pipe welded onto the outside of the innertank
Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside

Outlet of tank: DN40 DIN 11851
Agitator: yes
Top: 4,50 mm
Cylinder: 10,20 mm
Bottom: 8,30 mm

Internal diameter tank: 1.880 mm
Cylinder height: 1.580 mm
Total height of tank: 3.550 mm

SKU: 407465

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure
Konfiguration: single jacketed with heat-exchanger
Mobil tank: Nej
Övrig information: Chemistry; Upper bottom, Aisi 304 (1.4301); 4 support brackets, Fe; Slight corrosion of material inside the tank; some residues of previous content;motor-/gear is missing; we can’t give any
Övrig information2: guarantees about the agitator
Omrörare: Ja
Övertryck: 3,20 Bar
Total urtappning: Ja
Undertryck (vakuum): 3,20 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 5000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.580 mm
Invändig diameter: 1.880 mm
Total höjd: 3.550 mm

Tjocklek på tank
Botten: 8,30 mm
Cylinder: 10,20 mm
Topp: 4,50 mm

Mer
Isolerad: Nej