

5000 liter tank i Syrafast 316



154 000 SEK /st exkl moms

Additional information: Chemistry; Upper bottom made of stainless steel 304 (1.4301); 4 claws made of Fe; Slight material damage inside the vessel; some residues of previous content; motor-/gear is missing

Volumetric volume (L): 5.000 L

Pressure in tank: ATM - atmosferic

Max. pressure (Bar): 3,20 Bar

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Max Overpressure: 16 Bar

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: DN40 DIN 11851

Agitator: yes

Top: 4,50 mm

Cylinder: 10,20 mm

Bottom: 8,30 mm

Internal diameter tank: 1.880 mm

Cylinder height: 1.580 mm

Total height of tank: 3.550 mm

SKU: 283414

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure

Konfiguration: single jacketed with heat-exchanger

Mobil tank: Nej

Övrig information: Chemistry; Upper bottom, Aisi 304 (1.4301); 4 support brackets, Fe; Slight corrosion of material inside the tank; some residues of previous content; motor-/gear is missing; we can't give any

Övrig information2: guarantees about the agitator

Omrörare: Ja

Övertryck: 3,20 Bar

Total urtappning: Ja

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 5000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.580 mm

Invändig diameter: 1.880 mm

Total höjd: 3.550 mm

Tjocklek på tank

Botten: 8,30 mm

Cylinder: 10,20 mm

Topp: 4,50 mm

Mer

Isolerad: Nej