5000 liter tank i Syrafast 316



206 000 SEK /st exkl moms

Additional information: Food industry; Minor dents in the iso jacket; some residues of previous content
Volumetric volume (L): 5.000 L
Pressure in tank: pressure
Max. temperature (°C): 100 °C

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no

Total discharge: yes
Volume: 100 L
Max Overpressure: 5 Bar
Max. working temperature: 100 °C
Type HE on the cylinder: half pipe welded onto the outside of the innertank

Heat exchanger: RVS 304
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no

Position of manway: headside
Outlet of tank: 48
Agitator: yes
Number of revolutions: 460
Power: 0,75

Internal diameter tank: 1.700 mm
Outer diameter tank: 1.900 mm
Cylinder height: 2.250 mm
Total height of tank: 4.050 mm

SKU: 408719

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: isolert med varmeveksler
Max. arbetstemperatur: 100 °C
Mobil tank: Nej
Övrig information: Food industry; Smaller dents in the insulation jacket; some residues of previous content; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the
Övrig information2: agitator
Omrörare: Ja
Total urtappning: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 5000

Utrustning

Dokument finns: Nei, det er det ikke.
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank
Cylinderhöjd: 2.250 mm
Invändig diameter: 1.700 mm
Total höjd: 4.050 mm
Ytterdiameter: 1.900 mm

Omrörare
Kraft (kW): 0,75
Varvtal: 460

Mer
Värmeväxlare: RVS 304
Isolerad: Ja