

5000 liter tank i Syrafast 316



207,000,00 kr /st exkl moms

Additional information: Food industry; Smaller dents in the insulation jacket; some residues of previous content

Volumetric volume (L): 5.000 L

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 100 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 100 L

Max Overpressure: 5 Bar

Max. working temperature: 100 °C

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: 48

Agitator: yes

Number of revolutions: 460

Power: 0,75

Internal diameter tank: 1.700 mm

Outer diameter tank: 1.900 mm

Cylinder height: 2.250 mm

Total height of tank: 4.050 mm

SKU: 284680

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 100 °C

Mobil tank: Nej

Övrig information: Food industry; Smaller dents in the insulation jacket; some residues of previous content; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the

Övrig information2: agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 5000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Cylinderhöjd: 2.250 mm
Invändig diameter: 1.700 mm
Total höjd: 4.050 mm
Ytterdiameter: 1.900 mm

Omrörare

Kraft (kW): 0,75
Varvtal: 460

Mer

Värmeväxlare: RVS 304
Isolerad: Ja