

5000 liter tank i Syrafast 316



69 000 SEK /st exkl moms

Additional information: One of the feet with a height-adjustable screw; Manhole diameter approx. 510 mm; Tank with adhesions inside

Volumetric volume (L): 5.000 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: 70

Agitator: yes

Number of revolutions: 63

Power: 0,75

Internal diameter tank: 1.790 mm

Cylinder height: 2.000 mm

Total height of tank: 3.250 mm

SKU: 288698

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: single-skin

Mobil tank: Nej

Övrig information: One of the feet with a height-adjustable screw; Manhole diameter approx. 510 mm; Tank with adhesions inside; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 5000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 2.000 mm

Invändig diameter: 1.790 mm

Total höjd: 3.250 mm

Omrörare

Kraft (kW): 0,75

Varvtal: 63

Mer

Isolerad: Nej
