

## 5000 liter tank i Syrafast 316



**174,000,00 kr /st exkl moms**

**Additional information:** Food industry; Manhole diameter 490 mm; nameplate may no longer exist; half-coil around the lower cylinder area; adhesions inside the tank; bump at the insulation jacket

**Volumetric volume (L):** 5.000 L

**Pressure in tank:** ATM - atmosferic

**Max. temperature (°C):** 100 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 100 L

**Max Overpressure:** 5 Bar

**Max. working temperature:** 100 °C

**Type HE on the cylinder:** half pipe welded onto the outside of the innertank

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** no

**Flange for agitator:** no

**Position of manway:** in the bottom

**Outlet of tank:** 48

**Agitator:** yes

**Number of revolutions:** 24

**Power:** 2,20

**Internal diameter tank:** 1.700 mm

**Outer diameter tank:** 1.880 mm

**Cylinder height:** 2.150 mm

**Total height of tank:** 4.150 mm

**SKU:** 294019

Mer information

---