

5000 liter tank i Syrafast 316



81,000,00 kr /st exkl moms

Additional information: Cosmetics; 4 feet, Fe screwed to 4 support brackets, Fe; Propeller of the eccentric propeller agitator slightly bent

Volumetric volume (L): 5.000 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Position of manway: headside

Outlet of tank: flange DN50

Agitator: yes

Number of revolutions: 950

Power: 1,50

Internal diameter tank: 1.990 mm

Cylinder height: 1.500 mm

Total height of tank: 4.350 mm

SKU: 299304

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: single-skin

Mobil tank: Nej

Övrig information: Cosmetics; 4 feet, Fe screwed to 4 support brackets, Fe; Propeller of the eccentric propeller agitator slightly bent; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 5000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.500 mm

Invändig diameter: 1.990 mm

Total höjd: 4.350 mm

Omrörare

Kraft (kW): 1,50

Varvtal: 950

Mer

Isolerad: Nej
