5000 liter tank i Syrafast 316



82 000 SEK /st exkl moms

Additional information: Manhole, approx. 500 x 400 mm
Volumetric volume (L): 5.000 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 316 (V4A)

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Model: vertical

Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no
Total discharge: yes

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: cylinder

Outlet of tank: 78
Agitator: yes
Number of revolutions: 720 / 1440
Power: 1.7 / 7.0
Cylinder: 3 mm

Internal diameter tank: 1.500 mm
Cylinder height: 2.750 mm
Total height of tank: 4.400 mm

SKU: 706687

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmospheric
Konfiguration: single-skin
Mobil tank: Nej
Övrig information: Manhole, approx. 500 x 400 mm; we can't give any guarantees about the agitator
Omrörare: Ja
Total urtappning: Yes
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 5000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 2.750 mm
Invändig diameter: 1.500 mm
Total höjd: 4.400 mm

Omrörare

Kraft (kW): 1.7 / 7.0
Varvtal: 720 / 1440

Tjocklek på tank
Cylinder: 3 mm

Mer
Isolerad: Nej